

Exinda Network Orchestrator 4062 v2 is our most powerful branch office appliance designed for customers with rapidly growing bandwidth needs and require the flexibility to upgrade in the future. The 4062 v2 can be deployed as a 100 Mbps system and easily upgraded to 1 Gbps, with expandable network interfaces and remote management capabilities. If you're concerned about scaling to meet the future needs of your network, the 4062 v2 is for you.

Traffic Shaping	
Shaping Throughput	1 Gbps
Concurrent Flow	220,000
New Connection Rate	10,000/s
Packets Per Second	200,000/s
Traffic Policies	1024
Traffic Acceleration	
Acceleration Throughput	30 Mbps
Edge Cache Throughput	50 Mbps
Optimized Connections	6,000
Network Diagnostics	
APS Objects	250
SLA Objects	250
PDF Reports	60
Interface Capabilities	
Built in NICs	3 x 1G bypass bridge pair
Additional NIC Slots	1 full height expansion slot
Available NICs	Copper: 5 x 1G bypass bridge pair Fiber: 2 x 1G bypass bridge pair
Management Ports	RJ-45 serial console and dedicated
IPMI	Shared with dedicated management interface
Physical Characteristics	
Form Factor	1U rackmount
Dimensions (HxWxD)	44 mm x 436 mm x 300 mm (1.72" x 16.81" x 11.81")
Power	Internal - autoranging
Power Rating	17W @ 0.13A (Idle), 22W @ 0.16A (Max)
Weight	5.0 kg (11 lbs)
RAM	16GB (2 x 8GB DIMMs)
Data Store/Cache Size	SSD D3-S4510 960GB
Environment	10°C to 35°C (50°F to 95°F), 10% to 80% relative humidity



Talk to an Exinda appliance expert today

sales@gfi.com

www.gfi.com/exinda