

The Exinda Appliance 12063 is Exinda's large range data center grade appliance. Architected to serve the large data centers and service provider networks, the 12063 is built to scale with your business. With exceptional power and bandwidth capacity, our most powerful appliance can protect application SLAs no matter what the network throws at it. Built for companies and service providers with extremely high traffic volume and whose business depends on meeting and exceeding network application SLAs.

### Traffic Shaping

Shaping Throughput	15 Gbps
Concurrent Flows	1,800,000
New Connections Rate	38,000/s
Packets Per Second	1,800,000/s
Traffic Policies	4096

### Traffic Acceleration

Acceleration Throughput	2 Gbps
Edge Cache Throughput	500 Mbps
Optimized Connections	49,000

### Network Diagnostics

APS Objects	400
SLA Objects	400
PDF Reports	150

### Interface Capabilities

Built in NICs	None
Additional NIC Slots	4 full height and 3 half height expansion slots
Available NICs	<b>Copper:</b> 18 x 1G bypass bridge pair, 7 x 10G bypass bridge pair <b>Fiber:</b> 11 x 1G bypass bridge pair, 7 x 10G bypass bridge pair
Management Ports	DB-9 serial console and dedicated RJ-45 management interface
IPMI	Dedicated RJ-45 interface

### Physical Characteristics

Form Factor	2U rackmount
Dimensions (HxWxD)	87.3mm x 482mm x 756mm (3.44" x 18.98" x 29.75")
Power	Dual hot-plug redundant power - 750W
Power Rating	100–240 V AC autoranging, 50/60 Hz, 10A - 5A
Weight	31.5kg (69.45 lbs)
Data Store / Cache Size	1.6TB - SSD, RAID 1
Environment	Continuous operation: 10°C to 35°C (50°F to 95°F), 10% to 80% relative humidity

